

10GX32 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable



For more Information
please call

1-800-Belden1



Description:

23 AWG solid bare copper bonded-pair conductors, polyolefin insulation, patented H-spline center member, rip cord, PVC jacket.

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, 10 Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, PoE

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord: Yes

Overall Cabling

Overall Cabling Fillers: H-Spline Center Member

Overall Nominal Diameter: 0.295 in.

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)

Storage Temperature Range: -20°C To +80°C

Operating Temperature Range: -10°C To +75°C

Bulk Cable Weight: 40 lbs/1000 ft.

Max. Recommended Pulling Tension: 45 lbs.

10GX32 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

Min. Bend Radius (Install)/Minor Axis: 3 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CEC/C(UL) Specification:	CMR
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	08/20/2008
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	568-B.2-1 Category 6A

Flame Test

UL Flame Test:	UL1661 Riser
CSA Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Burial:	No
Sunlight Resistance:	No
Oil Resistance:	No
Non-halogenated:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	10GX33

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)
17.000

Nominal Velocity of Propagation:

VP (%)
64.000

Maximum Capacitance Unbalance (pF/100 m): 330

Maximum Delay:

Delay (ns/100 m)
538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
35.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
7.500

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
9.380

10GX32 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
4.000

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.100	75.3	73.3	73.2	71.2	20.000
4	3.800	66.3	64.3	62.5	60.5	23.000
8	5.300	61.8	59.8	56.4	54.4	24.500
10	5.900	60.3	58.3	54.4	52.4	25.000
16	7.500	57.2	55.2	49.8	47.8	25.000
20	8.400	55.8	53.8	47.4	45.4	25.000
25	9.400	54.3	52.3	45.0	43.0	24.300
31.25	10.500	52.9	50.9	42.4	40.4	23.600
62.5	15.000	48.4	46.4	33.4	31.4	21.500
100	19.100	45.3	43.3	26.2	24.2	20.100
200	27.600	40.8	38.8	13.2	11.2	18.000
250	31.100	39.3	37.3	8.3	6.3	17.300
300	34.300	38.1	36.1	3.9	1.9	16.800
350	37.200	37.1	35.1	N/A	N/A	16.300
400	40.100	36.3	34.3	N/A	N/A	15.900
450	42.700	35.5	33.5	N/A	N/A	15.500
500	45.300	34.8	32.8	N/A	N/A	15.200
550	47.700	34.2	32.2	N/A	N/A	14.900
600	50.100	33.6	31.6	N/A	N/A	14.700
625	51.200	33.4	31.4	N/A	N/A	14.500

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	70.8	68.8
4	100 ± 15	100 ± 15	58.8	56.8
8	100 ± 15	100 ± 15	52.7	50.7
10	100 ± 15	100 ± 15	50.8	48.8
16	100 ± 15	100 ± 15	46.7	44.7
20	100 ± 15	100 ± 15	44.8	42.8
25	100 ± 15	100 ± 15	42.8	40.8
31.25	100 ± 15	100 ± 15	40.9	38.9
62.5	100 ± 15	100 ± 15	34.9	32.9
100	100 ± 22	100 ± 15	30.8	28.8
200	100 ± 22	100 ± 15	24.8	22.8
250	100 ± 32	100 ± 15	22.8	20.8
300	100 ± 32	100 ± 15	21.3	19.3
350	100 ± 32	100 ± 15	19.9	17.9
400	100 ± 32	100 ± 15	18.8	16.8
450	100 ± 32	100 ± 15	17.7	15.7
500	100 ± 32	100 ± 15	16.8	14.8
550	100 ± 32	100 ± 15	16.0	14.0
600	100 ± 32	100 ± 15	15.2	13.2
625	100 ± 32	100 ± 15	14.9	12.9

Premise Cable Electrical Table 3:

Frequency (MHz)	Min. PSANEXT (dB)	Min. PSAELFEXT (dB)	Min. TCL (dB)	Min. ELTCTL (dB)
1	67	67	40	35
4	67	67	40	23
8	67	61.1	40	16.9
10	67	59.2	40	15.0

10GX32 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

16	67	55.1	38	10.9
20	67	53.2	37	9.0
25	67	51.2	36	7.0
31.25	67	49.3	35.1	
62.5	66.6	43.3	32	
100	63.5	39.2	30	
200	59.0	33.2	27	
250	57.5	31.2	26	
300	56.3	29.7		
350	55.3	28.3		
400	54.5	27.2		
450	53.7	26.1		
500	53.0	25.2		
550	52.4	24.4		
600	51.8	23.6		
625	51.6	23.3		

Notes (Overall)

Notes: Belden IBDN. Jacket sequentially marked at 2 ft. intervals. US Patent #'s 6297454-B1; 5606151; 5734126; 5789711.

Notes (Cont'd.): 0.295" cable dimension per UL 6@1 equivalent diameter.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
10GX32 0061000	1,000 FT	44.000 LB	BLUE, LIGHT	C	4 PR #23 PP FRPVC
10GX32 0081000	1,000 FT	44.000 LB	GRAY	C	4 PR #23 PP FRPVC
10GX32 0091000	1,000 FT	44.000 LB	WHITE	C	4 PR #23 PP FRPVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 03-16-2009

© 2008 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.